

# XRRGI®

# 6

# 9

## ELECTRIFYING HEAT

Max. noise level dB(A)	49	49
Dimensions (L x W x H) cm	92 x 64 x 96	92 x 64 x 96
Floor area m <sup>2</sup>	0.59	0.59
Weight kg	440	440
Warranty period years	5	5
Service interval hours	10,000	10,000
Fuels: natural gas (all qualities), propane, butane	yes	yes
Electrical output (modulating) kW	2.5–6	4–9
Thermal output kW	8–13.5	12–20
Power consumption (gas) kW	21	31
Electrical efficiency	29.5 %	29.5 %
Thermal efficiency (excluding optional condenser)	63.5 %	63.5 %
Total efficiency (excluding optional condenser)	93 %	93 %
Flow temperature (constant) °C	80–85	80–85
Max. Return temperature (variable) °C	5–75	5–75
Maximum exhaust gas temperature °C	100	100
Emissions	CO: < 150 mg/Nm <sup>3</sup> NOX: < 350 mg/Nm <sup>3</sup>	CO: < 50 mg/Nm <sup>3</sup> NOX: < 100 mg/Nm <sup>3</sup>
Primary energy saving PES (EU Directive, verification in accordance with DIN 4709)	20.3 %	22.4 %

All values are net and have been certified by an independent inspection body.

[www.ecpower.eu](http://www.ecpower.eu)

